



# Ferox Benefits

Revised: January 2005

A majority of the benefits obtained from Ferox products are derived from the combustion surface and deposit surface modifiers included in the Ferox formulation. Each major Ferox benefit is listed below with a short technical explanation.

## **Removes Deposits**

The catalytic components in Ferox cause deposit removal by interacting with the surface of the deposit and lowering the activation energy of its chemical bonds. This allows the release of carbon atoms in the form of CO<sub>2</sub> to occur at the lower temperatures found at the deposit surface.

## **Inhibits Deposit Formation**

The catalytic components in Ferox inhibit the agglomeration process, which the combustion products undergo when forming heavy deposits. The agglomeration process is stopped at the primary and secondary particle formation phase resulting in smaller, lighter particles.

## **Decreases Fuel Consumption**

This benefit shows up as the deposits are removed. This is due to the more efficient conversion of the fuel to CO<sub>2</sub> and the fact that deposit material that absorbs and protects the fuel from being completely combusted is being destroyed and removed.

## **Emissions Are Reduced**

The primary source for harmful emissions is the carbon deposits themselves. With the deposits removed there is a drastic reduction in the emissions of CO, NO<sub>x</sub>, SO<sub>x</sub>, HC and particulates.

## **Carbon Content Of Ash Will Drop**

With the catalytic components interfering with the agglomeration of the combustion products and promoting CO<sub>2</sub> production, less carbon is available to end up in the ash complex. This also results in a smaller amount of ash being produced.

## **Exhaust Will Be Cooler**

Fuel has a limited amount of energy that is derived through the production of CO<sub>2</sub>. The catalytic components in Ferox promote the production of CO<sub>2</sub>. When more of a fuel's energy is released during the combustion phase less is available to be released during the exhaust phase. The difference in energy release correlates to a temperature difference. A lower temperature during the exhaust phase, due to decreased CO<sub>2</sub> production during that phase, results in cooler exhaust.

## **Extends Oil Life**

Ferox treated fuels tend to produce smaller and less abrasive particles which in connection with the removal of carbon deposits results in cleaner longer lasting oil. These results lead to reduced engine wear and less maintenance time.

## **Extends Equipment Life**

Equipment life is increased due to lack of deposit buildup, cleaner oil and reduced friction. Injectors, valves, rings and other associated parts show little sign of wear even after extended use.

## **Octane-Requirement Decrease**

In gasoline applications a lower octane fuel can be used, due to carbon deposit removal, and still provide the same performance as with previous higher-octane fuels.

## **Inhibits Stratification, Sludge Formation and Inhibits Corrosion**

Due to Ferox Dispersant and Corrosion Inhibitor components.